



Industry Tag

FEATURES

- The 25mm Tag with multi read/write capability is very small in size and is made of ABS to meet all endurance requirements in terms of heat, harsh environments and chemical resistance.
- Perform in the harshest environments, including harsh chemicals, painting processes & outdoor exposure.
- Dust & Waterproof.
- Flexible Read/Write Range (reader dependant).
- Insensitive to almost all non metallic materials.

APPLICATIONS

- Being used in industrial environments, as well as in asset tracking applications
- It has been widely used in supply chain, service industries, distribution logistics and manufacturing companies to identify goods & objects in an industrial environment.
- Can be used to read through obstructions, including water, plastics, concrete and more.
- Suitable for factory floor manufacturing applications because of rugged construction (IP Rating).

Chip Type:	HitagS 256 bit 125 KHz	
	256 bits, organized in 16 blocks of 4 byte each	
	Data retention of 10 years	
	Write endurance 100.000 cycles	
Mechanical:	Outer Dia.	25mm
	Thickness	2.3mm
	Material	ABS
	Colour	Blue/Black
	Weight	<1.5 gms.
	Antenna Type	Wire Antenna
Electrical:	Operating Frequency	125 KHz
	Operating mode	Passive (battery-less transponder)
Ingress Protection:	IP67	
Thermal:	Storage Temp.	-20°C to +85°C
	Operating Temp.	-20°C to 85°C
	Transport Conditions	-40°C to 85°C
Part Number:	11N01	
Options:	Other IC type, Size, Shape & Colour on request	
	Available with other plastic material e.g. PC/ABS	

*Preliminary Data Sheet: Certain specification subject to change.